



|                              | DLED10-BI   | DLED10-D   | DLED12-BI-DMX                  | DLED30-D                       |
|------------------------------|---|--|--------------------------------|--------------------------------|
| <b>Preferred use:</b>        | MOBIL   | MOBIL  | STUDIO                         | STUDIO                         |
| <b>LED Chip / Wattage</b>    | 220 W bicolor   | 300 W daylight   | 220 W bicolor                  | 300 W daylight                 |
| <b>Ballast</b>               | separate (DT10-BI),<br>DMX as standard                        | separate (DT10),<br>DMX as standard                            | integrated,<br>DMX as standard | integrated,<br>DMX as standard |
| <b>Cable to light head</b>   | separate (DPOW10)   | separate (DPOW10)  | no cables                      | no cables                      |
| <b>Focusing (flood/spot)</b> | 50° - 4°  | 50° - 4°   | 60° - 5°                       | 65° - 4°                       |
| <b>Size</b>                  | 389 x 198 x 356 mm (light head)<br>369 x 83 x 80 mm (ballast) | 389 x 198 x 356 mm (light head)<br>420 x 148 x 68 mm (ballast) | 485 x 324 x 543 mm             | 485 x 337 x 604 mm             |
| <b>Weight</b>                | 4,2 kg (light head)<br>2,2 kg (ballast)                       | 4,2 kg (light head)<br>5,2 kg (ballast)                        | 11 kg                          | 16,5 kg                        |
| <b>Lux @ 3m (flood)</b>      | 1.400 (daylight settings)                                     | 1.900  | 933 (daylight setting)         | 1.300                          |
| <b>Lux @ 3m (spot)</b>       | 5.466 (daylight setting)                                      | 12.500   | 10100 (daylight setting)       | 18.000                         |
| <b>OPTION</b>                |   |  | Pole Operation yoke            | Pole Operation yoke            |